

SOFT PLASTICS ADHESIVE
 Revision Number 1.01

Revision Date 14-Oct-2018
Supersedes Date: 30-Apr-2018

Section 1: Identification: Product identifier and chemical identity

Product Identifier

Product Name SOFT PLASTICS ADHESIVE

Product Code(s)
 30803650
 30803650

Other means of identification

Proper Shipping Name Adhesives

UN Number UN1133

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Adhesives

Uses advised against No information available

Details of manufacturer or importer

Supplier
 Bostik Australia Pty Ltd
 51-71 High Street,
 Thomastown Victoria
 Australia
 Tel: 613 9279-9333
 Fax: 613 9279-9342

Manufacturer
 Bostik Limited
 Common Rd
 ST16 3EH
 Stafford UK
 Tel: +44 (1785) 27 26 25
 Fax: +44 (1785) 25 72 36

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Based on available information, this material is classified as hazardous according to criteria of Safe Work Australia

Flammable liquids	Category 2 - (H225)
Serious eye damage/eye irritation	Category 2A - (H319)
Skin sensitization	Category 1 - (H317)
Specific target organ toxicity (single exposure)	Category 3 - (H336)

Label Elements

Flame
 Exclamation mark

Safety Data Sheet

SOFT PLASTICS ADHESIVE
Revision Number 1.01

Revision Date 14-Oct-2018
Supersedes Date: 30-Apr-2018



Signal word
DANGER

Hazard statements

H225 - Highly flammable liquid and vapor
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
AUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Use only outdoors or in a well-ventilated area
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool
Use explosion-proof electrical/ ventilating/ lighting/ equipment
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell
In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Causes mild skin irritation
Harmful to aquatic life with long lasting effects
In use may form flammable/explosive vapor-air mixture

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S5

Label requirements in accordance with SUSMP

CAUTION
KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Safety Data Sheet

SOFT PLASTICS ADHESIVE
Revision Number 1.01

Revision Date 14-Oct-2018
Supersedes Date: 30-Apr-2018

Substance

Not applicable

Mixture

Chemical Name	CAS No.	Weight-%
Acetone	67-64-1	30 - 40%
Methyl ethyl ketone	78-93-3	30 - 40%
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	ECKNOWN	0 - 10%
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	25068-38-6	0 - 10%
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

FIRST AID

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water. Drink 1 or 2 glasses of water. Call a physician or poison control center immediately. Clean mouth with water and drink afterwards plenty of water.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media Do not use straight streams. CAUTION: Use of water spray when fighting fire may be inefficient.

Special exposure hazards in a fire

Safety Data Sheet

SOFT PLASTICS ADHESIVE
Revision Number 1.01

Revision Date 14-Oct-2018
Supersedes Date: 30-Apr-2018

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.

Hazardous Combustion Products Carbon oxides.

Protective equipment and precautions for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code •3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Keep people away from and upwind of spill/leak.

Other Information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil.

Methods and material for containment and cleaning up

Methods for containment Dike far ahead of spill; use dry sand to contain the flow of material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take up mechanically, placing in appropriate containers for disposal.

Precautions to prevent secondary hazards

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

General hygiene considerations Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

Safety Data Sheet

SOFT PLASTICS ADHESIVE
Revision Number 1.01

Revision Date 14-Oct-2018
Supersedes Date: 30-Apr-2018

Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

Incompatible materials None known based on information supplied.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical Name	Australia
Acetone 67-64-1	500 ppm TWA 1185 mg/m ³ TWA 1000 ppm STEL 2375 mg/m ³ STEL
Methyl ethyl ketone 78-93-3	150 ppm TWA 445 mg/m ³ TWA 300 ppm STEL 890 mg/m ³ STEL

OEL as published by Safe Work Australia

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eyeface protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Hand protection Wear suitable gloves. Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical State Liquid
Appearance Paste
Color Clear
Odor Characteristic
Odor Threshold No information available

Safety Data Sheet

SOFT PLASTICS ADHESIVE
Revision Number 1.01

Revision Date 14-Oct-2018
Supersedes Date: 30-Apr-2018

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	approx. 56 °C	
Flash Point	approx. -20 °C	
Evaporation Rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor Pressure	No data available	
Vapor Density	No data available	
Relative Density	0.87	
Water Solubility	No data available	None known
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Kinematic Viscosity		
Dynamic Viscosity	No data available	
Explosive properties	No information available	
Oxidizing properties	No information available	
<u>Other information</u>		
Solid content (%)	No information available	
VOC (volatile organic compound)	No information available	
Density	No information available	

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge Yes.

Possibility of Hazardous Reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible Materials

Incompatible materials None known based on information supplied.

Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

Section 11: Toxicological information

Safety Data Sheet

SOFT PLASTICS ADHESIVE
Revision Number 1.01

Revision Date 14-Oct-2018
Supersedes Date: 30-Apr-2018

Acute Toxicity

Information on likely routes of exposure

Product Information

Inhalation	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Causes serious eye irritation. May cause redness, itching, and pain.
Skin contact	May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause irritation. Prolonged contact may cause redness and irritation. Causes mild skin irritation.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Itching. Rashes. Hives. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document
ATEmix (oral) 7,320.00 mg/kg

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	= 5800 mg/kg (Rat)	>15800 mg/Kg (rat)	= 79 mg/l(Rat) 4 h
Methyl ethyl ketone	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	LD50 (rat) > 2000 mg/kg OECD 420	>2000 mg/Kg (rat)	-

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	May cause sensitization by skin contact.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Safety Data Sheet

SOFT PLASTICS ADHESIVE
Revision Number 1.01

Revision Date 14-Oct-2018
Supersedes Date: 30-Apr-2018

Chemical Name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.2 mg/l 96Hr (Oncorhynchus mykiss)	-	2.7 mg/l 48hr Daphnia Magna

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulative potential There is no data for this product.

Component Information

Chemical Name	Partition coefficient
Acetone 67-64-1	-0.24
Methyl ethyl ketone 78-93-3	0.3
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	3.26

Mobility

Mobility in soil No information available.

Mobility No information available.

Other Adverse Effects

Other Adverse Effects No information available.

Chemical Name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Endocrine disrupting potential
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	Group III Chemical	-	-

Section 13: Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Section 14: Transport information

ADG

UN Number

UN1133

Safety Data Sheet

SOFT PLASTICS ADHESIVE
Revision Number 1.01

Revision Date 14-Oct-2018
Supersedes Date: 30-Apr-2018

Proper shipping name Adhesives
Hazard Class 3
Packing Group III
Special Provisions 223, *
Description UN1133, Adhesives, 3, III

Hazchem code •3Y

IATA

UN Number UN1133
Transport hazard class(es) 3
Packing Group III
ERG Code 3L
Special Provisions A3
Limited Quantity (LQ) 10 L
Description UN1133, Adhesives, 3, III

IMDG

UN Number UN1133
Transport hazard class(es) 3
Packing Group III
EmS-No. F-E, S-D
Limited Quantity (LQ) 5 L
Special Provisions 223, 955
Marine Pollutant Np
Description UN1133, Adhesives, 3, III, (-20°C c.c.)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S5

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III
Liquids with flash points <61°C kept above their boiling points
at ambient conditions

Threshold quantity (T)

50 000
200

National pollutant inventory

Subject to reporting requirement

Chemical Name	National pollutant inventory
Acetone 67-64-1	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

Safety Data Sheet

SOFT PLASTICS ADHESIVE
Revision Number 1.01

Revision Date 14-Oct-2018
Supersedes Date: 30-Apr-2018

Methyl ethyl ketone 78-93-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
--------------------------------	---

International Inventories

AICS	Listed
NZIoC	Not Listed
ENCS	Listed
IECSC	Listed
KECL	Listed
PICCS	Listed

Legend:

AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision Date 14-Oct-2018

Revision Note

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Section 11: Toxicological information

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet