



SAFETY DATA SHEET

STP® Complete Fuel System Cleaner 400ml (Diesel)

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STP® Complete Fuel System Cleaner 400ml (Diesel)
Product number 65400

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fuel additive.
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Armored Auto UK Ltd
 Unit 16
 Rassau Industrial Estate
 Ebbw Vale
 Gwent
 NP23 5SD
 UK
 Tel: +44 1495 350234
 Fax: +44 1495 350431
 euregulatory@eu.spectrumbrands.com

1.4. Emergency telephone number

Emergency telephone +44 1495 350234
 Monday - Thursday: 0830 - 1700
 Friday: 0830 - 1530

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Asp. Tox. 1 - H304
Environmental hazards Not Classified

Human health Pneumonia may be the result if vomited material containing solvents reaches the lungs.

2.2. Label elements

Pictogram



Signal word Danger

STP® Complete Fuel System Cleaner 400ml (Diesel)

Hazard statements	H304 May be fatal if swallowed and enters airways.
Precautionary statements	P102 Keep out of reach of children. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics, Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Distillates (petroleum), hydrotreated heavy paraffinic
Supplementary precautionary statements	P405 Store locked up.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics			50 - 100%
CAS number: —	EC number: 926-141-6	REACH registration number: 01-2119456620-43-XXXX	
Classification Asp. Tox. 1 - H304			
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			5 - <10%
CAS number: —	EC number: 918-481-9		
Classification Flam. Liq. 3 - H226 Asp. Tox. 1 - H304			
2-ethylhexan-1-ol			2 - <3%
CAS number: 104-76-7	EC number: 203-234-3	REACH registration number: 01-2119487289-20-XXXX	
Classification Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335			

STP® Complete Fuel System Cleaner 400ml (Diesel)

Distillates (petroleum), hydrotreated heavy paraffinic		1 - <2.5%
CAS number: 64742-54-7	EC number: 265-157-1	REACH registration number: 01-2119484627-25-XXXX
Classification		
Asp. Tox. 1 - H304		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Inhalation	If throat irritation or coughing persists, proceed as follows. Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if symptoms are severe or persist.
Skin contact	Remove contaminated clothing and rinse skin thoroughly with water. Continue to rinse for at least 15 minutes. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if symptoms are severe or persist after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Drowsiness. Dizziness.
Ingestion	May cause discomfort if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. Keep affected person under observation.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	--

STP® Complete Fuel System Cleaner 400ml (Diesel)

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters Use protective equipment appropriate for surrounding materials. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all ignition sources if safe to do so. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Do not touch or walk into spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Use only non-sparking tools. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Keep away from heat, sparks and open flame. Provide adequate ventilation.

Advice on general occupational hygiene Avoid contact with eyes and prolonged skin contact. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep away from heat, sparks and open flame. Take precautionary measures against static discharges.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Ingredient comments No exposure limits known for ingredient(s).

STP® Complete Fuel System Cleaner 400ml (Diesel)

Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64742-54-7)

PNEC

- Oral; 9.33 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and lighting equipment.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Do not smoke in work area. Wash promptly with soap and water if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked.

Environmental exposure controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Dark brown.
Odour	Characteristic.
Odour threshold	Not determined.
pH	Not determined.
Melting point	Not relevant.
Initial boiling point and range	Not determined.
Flash point	72°C
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not relevant.

STP® Complete Fuel System Cleaner 400ml (Diesel)

Upper/lower flammability or explosive limits	Not relevant.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	0.8142 g/cm ³
Bulk density	Not determined.
Partition coefficient	Not determined.
Auto-ignition temperature	Not relevant.
Decomposition Temperature	Not relevant.
Viscosity	Not determined.
Explosive properties	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

9.2. Other information

Other information	No information required.
-------------------	--------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Will not polymerise.
------------------------------------	----------------------

10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time.
---------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	None at ambient temperatures. Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Oxides of nitrogen.
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD ₅₀)	Based on available data the classification criteria are not met.
--------------------------------	--

Acute toxicity - dermal

Notes (dermal LD ₅₀)	Based on available data the classification criteria are not met.
----------------------------------	--

Acute toxicity - inhalation

STP® Complete Fuel System Cleaner 400ml (Diesel)

Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
ATE inhalation (vapours mg/l)	385.2
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Based on available data the classification criteria are not met.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Based on available data the classification criteria are not met.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Kinematic viscosity ≤ 20.5 mm ² /s. May be fatal if swallowed and enters airways.

Toxicological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 15,000.0

Species Rat

Notes (oral LD₅₀) REACH dossier information. Read-across data.

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,160.0

Species Rabbit

Notes (dermal LD₅₀) REACH dossier information. Read-across data.

ATE dermal (mg/kg) 3,160.0

Acute toxicity - inhalation

STP® Complete Fuel System Cleaner 400ml (Diesel)

Acute toxicity inhalation
(LC₅₀ vapours mg/l)

4,951.0

Species

Rat

Notes (inhalation LC₅₀)

REACH dossier information. Read-across data.

ATE inhalation (vapours mg/l)

4,951.0

Skin corrosion/irritation

Animal data

Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2).
Oedema score: Very slight oedema - barely perceptible (1). REACH dossier information. Read-across data.

Serious eye damage/irritation

Serious eye damage/irritation

Dose: 0.1 ml, 1 second, Rabbit Not irritating. REACH dossier information. Read-across data.

Skin sensitisation

Skin sensitisation

Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information. Read-across data.

Germ cell mutagenicity

Genotoxicity - in vitro

Gene mutation: Negative. REACH dossier information. Read-across data.

Genotoxicity - in vivo

Chromosome aberration: Negative. REACH dossier information. Read-across data.

Carcinogenicity

Carcinogenicity

NOAEC 1100 mg/m³, Inhalation, Mouse REACH dossier information. Read-across data.

Reproductive toxicity

Reproductive toxicity - fertility

Fertility, One-generation study - NOAEL 750 mg/kg/day, Oral, Rat F1 REACH dossier information. Read-across data.

Reproductive toxicity - development

Maternal toxicity: - NOAEL: >= 5220 mg/m³, Inhalation, Rat REACH dossier information.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure

NOAEC > 10400 mg/m³, Inhalation, Rat REACH dossier information. Read-across data.

Aspiration hazard

Aspiration hazard

2.4 cSt @ 20°C Asp. Tox. 1 - H304

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg)

15,000.0

Species

Rat

Notes (oral LD₅₀)

REACH dossier information. Read-across data.

ATE oral (mg/kg)

15,000.0

Acute toxicity - dermal

STP® Complete Fuel System Cleaner 400ml (Diesel)

Acute toxicity dermal (LD₅₀ mg/kg) 3,160.0

Species Rabbit

Notes (dermal LD₅₀) REACH dossier information. Read-across data.

ATE dermal (mg/kg) 3,160.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 9.3

Species Rat

Notes (inhalation LC₅₀) REACH dossier information. Read-across data.

ATE inhalation (dusts/mists mg/l) 9.3

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2). Oedema score: No oedema (0). REACH dossier information. Read-across data.

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Read-across data. Not irritating.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information. Read-across data.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information. Read-across data.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information. Read-across data.

Carcinogenicity

Carcinogenicity NOAEC >= 138 mg/m³, Inhalation, Rat REACH dossier information. Read-across data.

Reproductive toxicity

Reproductive toxicity - fertility Fertility - NOAEC >=2200 mg/m³, Inhalation, Rat P REACH dossier information. Read-across data.

Reproductive toxicity - development Developmental toxicity: - NOAEL: >= 5220 mg/m³, Inhalation, Rat REACH dossier information.

Aspiration hazard

Aspiration hazard 1.8 cSt @ 20°C/68°F REACH dossier information.

2-ethylhexan-1-ol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,290.0

Species Rat

STP® Complete Fuel System Cleaner 400ml (Diesel)

Notes (oral LD₅₀)	REACH dossier information.
ATE oral (mg/kg)	3,290.0
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	3,000.0
Species	Rat
Notes (dermal LD₅₀)	REACH dossier information.
ATE dermal (mg/kg)	3,000.0
<u>Acute toxicity - inhalation</u>	
ATE inhalation (vapours mg/l)	11.0
<u>Skin corrosion/irritation</u>	
Animal data	Primary dermal irritation index: 6.75 Dose: 0.5 ml, 4 hours, Rabbit REACH dossier information. Highly irritating.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Irritating.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Gene mutation: Negative. REACH dossier information.
<u>Carcinogenicity</u>	
Carcinogenicity	NOAEL 500 mg/kg/day, Oral, Rat REACH dossier information.
<u>Reproductive toxicity</u>	
Reproductive toxicity - development	Developmental toxicity: - NOAEL: 2520 mg/kg/day, Dermal, Rat REACH dossier information.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	NOAEL 250 mg/kg/day, Oral, Rat REACH dossier information.
<u>Aspiration hazard</u>	
Aspiration hazard	4.3 mPa s @ 40°C/104°F REACH dossier information.
<u>Distillates (petroleum), hydrotreated heavy paraffinic</u>	
<u>Acute toxicity - oral</u>	
Notes (oral LD₅₀)	LD ₅₀ > 5000 mg/kg, Rat, REACH dossier information. Based on available data the classification criteria are not met.
<u>Acute toxicity - dermal</u>	
Notes (dermal LD₅₀)	LD ₅₀ > 2000 mg/kg, Rabbit, REACH dossier information. Based on available data the classification criteria are not met.
<u>Skin corrosion/irritation</u>	
Animal data	Dose: 0.5 ml, 24 hours, Rabbit Erythema/eschar score: Very slight erythema - barely perceptible (1). Oedema score: Very slight oedema - barely perceptible (1). REACH dossier information. Not irritating.

STP® Complete Fuel System Cleaner 400ml (Diesel)

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Not irritating.

Skin sensitisation

Skin sensitisation Buehler test - Guinea pig: Not sensitising. REACH dossier information.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. REACH dossier information.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information.

Carcinogenicity

Carcinogenicity REACH dossier information. No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEL $\geq$ 1000 mg/kg/day, Dermal, Mouse P REACH dossier information. Based on available data the classification criteria are not met.

Reproductive toxicity - development Maternal toxicity: - LOAEL: 125 mg/kg/day, Dermal, Rat REACH dossier information.

Aspiration hazard

Aspiration hazard 1.99 - 847 cSt @ 40°C REACH dossier information.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity Not considered toxic to fish. However, large or frequent spills may have hazardous effects on the environment.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout) REACH dossier information.

Acute toxicity - aquatic invertebrates EL₅₀, 48 hours: > 1000 mg/l, Daphnia magna REACH dossier information.

Acute toxicity - aquatic plants EL₅₀, 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata REACH dossier information.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOELR, 28 days: 0.173 mg/l, Oncorhynchus mykiss (Rainbow trout) QSAR REACH dossier information.

Chronic toxicity - aquatic invertebrates NOELR, 21 days: 1.22 mg/l, Daphnia magna QSAR REACH dossier information.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Acute aquatic toxicity

STP® Complete Fuel System Cleaner 400ml (Diesel)

Acute toxicity - fish LL₅₀, 96 hours: > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout)
REACH dossier information.

Acute toxicity - aquatic invertebrates EL₅₀, 48 hours: > 1000 mg/l, Daphnia magna
REACH dossier information.

Acute toxicity - aquatic plants EL₅₀, 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata
REACH dossier information.

Acute toxicity - microorganisms EL₅₀, 48 hours: > 1000 mg/l, Tetrahymena pyriformis
REACH dossier information.
QSAR

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOELR, 28 days: 0.101 mg/l, Oncorhynchus mykiss (Rainbow trout)
REACH dossier information.
QSAR

Chronic toxicity - aquatic invertebrates NOELR, 21 days: 0.176 mg/l, Daphnia magna
REACH dossier information.
QSAR

2-ethylhexan-1-ol

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 17.1 mg/l, Leuciscus idus (Golden orfe)
REACH dossier information.

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 39 mg/l, Daphnia magna
REACH dossier information.

Acute toxicity - aquatic plants EC₅₀, 72 hours: 11.5 mg/l, Scenedesmus subspicatus
REACH dossier information.

Distillates (petroleum), hydrotreated heavy paraffinic

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: > 100 mg/l, Pimephales promelas (Fat-head Minnow)
NOEL, 96 hours: ≥ 100 mg/l, Pimephales promelas (Fat-head Minnow)
REACH dossier information.

Acute toxicity - aquatic invertebrates LL₅₀, 24, 48, 72, 96 hours: > 10000 mg/l, Gammarus pulex
REACH dossier information.

Acute toxicity - aquatic plants NOEL, 72 hours: ≥ 100 mg/l, Pseudokirchneriella subcapitata
REACH dossier information.

Acute toxicity - microorganisms NOEL, 10 minutes: > 1.93 mg/l, Photobacterium phosphoreum
REACH dossier information.

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEL, 21 days: 10 mg/l, Daphnia magna
REACH dossier information.

12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

STP® Complete Fuel System Cleaner 400ml (Diesel)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradation	Water - Degradation ~ 5%: 3 days
	Water - Degradation 69: 28 days
	REACH dossier information.
	Readily biodegradable but failing the 10-day window.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation	Water - Degradation 80%: 28 days
	REACH dossier information.
	Read-across data.
	Readily biodegradable but failing the 10-day window.

2-ethylhexan-1-ol

Biodegradation	Water - Degradation 79 - 99.9%: 2 weeks
	REACH dossier information.
	The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Partition coefficient Scientifically unjustified. REACH dossier information.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

2-ethylhexan-1-ol

Bioaccumulative potential BCF: 25.33, REACH dossier information.

Partition coefficient log Pow: 2.9 REACH dossier information.

12.4. Mobility in soil

Mobility The product is soluble in water.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Mobility The product has poor water-solubility.

Surface tension 26.4 mN/m @ 25°C

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Mobility The product contains organic solvents which will evaporate easily from all surfaces. The product contains substances which are insoluble in water and which sediment in water systems.

STP® Complete Fuel System Cleaner 400ml (Diesel)

Surface tension 25.3 mN/m @ 25°C/77°F REACH dossier information.

2-ethylhexan-1-ol

Surface tension 47 mN/m @ 20°C/68°F REACH dossier information.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

STP® Complete Fuel System Cleaner 400ml (Diesel)

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.

IMDG: International Maritime Dangerous Goods.

IATA: International Air Transport Association.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ATE: Acute Toxicity Estimate.

DNEL: Derived No Effect Level.

LC₅₀: Lethal Concentration to 50 % of a test population.

LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

BCF: Bioconcentration Factor.

Classification procedures according to Regulation (EC) 1272/2008

Asp. Tox. 1 - H304: Calculation method., Expert judgement.

Revision comments

Section 2: Hazards identification // 2.2. Label elements. Section 3: Composition/information on ingredients // 3.2 Mixtures. Section 8: Exposure controls/personal protection // 8.1. Control parameters. Section 11: Toxicological information // 11.1. Information on toxicological effects. Section 12: Ecological information // 12.1. Toxicity. Section 12: Ecological information // 12.2. Persistence and degradability. Section 12: Ecological information // 12.3. Bioaccumulative potential. Section 12: Ecological information // 12.4. Mobility in soil.

Revision date

26/06/2017

Revision

7

Supersedes date

01/06/2017

SDS number

131

Hazard statements in full

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

STP® Complete Fuel System Cleaner 400ml (Diesel)

The information supplied here is accurate to the best knowledge and belief of Armored Auto UK Ltd, it is however, not intended as a warranty or representation, and should not be construed as such, for which Armored Auto UK Ltd assumes any legal responsibility. Any information or advice obtained from Armored Auto UK Ltd other than by means of this publication, and whether relating to Armored Auto UK Ltd's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Armored Auto UK Ltd when used instead of, or in conjunction with materials supplied by Armored Auto UK Ltd, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Armored Auto UK Ltd accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.