



SAFETY DATA SHEET
GUNK ENGINE DEGREASANT SPRAY AEROSOL

Page: 1

Compilation date: 02/04/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: GUNK ENGINE DEGREASANT SPRAY AEROSOL

Product code: 6731

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Granville Oil & Chemicals Ltd.
Unit 29 Goldthorpe Industrial Estate
Goldthorpe
Rotherham
South Yorkshire
S63 9BL
United Kingdom

Tel: +44 (0)1709 890099

Fax: +44 (0)1709 891121

Email: technical@granvilleoil.com

1.4. Emergency telephone number

Emergency tel: +44 (0)1709 890099
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F+: R12; Xi: R38; N: R51/53; -: R66; -: R67

Classification under CLP: Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; -: H229; Skin Irrit. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H336

Most important adverse effects: Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CLP:

Hazard statements: H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.

[cont...]

SAFETY DATA SHEET

GUNK ENGINE DEGREASANT SPRAY AEROSOL

Page: 2

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

GHS09: Environmental



Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P211: Do not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Label elements under CHIP:

Hazard symbols: Extremely flammable.

Irritant.

Dangerous for the environment.



Risk phrases: R12: Extremely flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe spray.

S24/25: Avoid contact with skin and eyes.

S29: Do not empty into drains.

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

[cont...]

SAFETY DATA SHEET
GUNK ENGINE DEGREASANT SPRAY AEROSOL

Page: 3

2.3. Other hazards

Other hazards: In use, may form flammable / explosive dust-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PROPANE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-827-9	74-98-6	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%

BUTANE

203-448-7	106-97-8	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
-----------	----------	---	-------------------------------------	--------

KEROSINE - UNSPECIFIED - KEROSINE (PETROLEUM), SWEETENED - REACH registered number(s): 01-2119502385-46

294-799-5	91770-15-9	Xn: R65; N: R51/53	Asp. Tox. 1: H304; Aquatic Chronic 2: H411	10-30%
-----------	------------	--------------------	--	--------

KEROSINE - UNSPECIFIED - KEROSINE (PETROLEUM), HYDRODESULPHURIZED - REACH registered number(s): 01-2119462828-25

265-184-9	64742-81-0	Xn: R65; N: R51/53	Asp. Tox. 1: H304; Aquatic Chronic 2: H411	10-30%
-----------	------------	--------------------	--	--------

ISOBUTANE

200-857-2	75-28-5	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	---------	---	-------------------------------------	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

[cont...]

SAFETY DATA SHEET
GUNK ENGINE DEGREASANT SPRAY AEROSOL

Page: 4

Ingestion: There may be irritation of the throat.

Inhalation: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. If outside do not approach from downwind.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may produce sparks. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

[cont...]

SAFETY DATA SHEET
GUNK ENGINE DEGREASANT SPRAY AEROSOL

Page: 5

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PROPANE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1800 mg/m3	7200 mg/m3	-	-

BUTANE

UK	1450 mg/m3	1810 mg/m3	-	-
----	------------	------------	---	---

ISOBUTANE

UK	2400 mg/m3	9600 mg/m3	-	-
----	------------	------------	---	---

DNEL/PNEC Values

Hazardous ingredients:

KEROSINE - UNSPECIFIED - KEROSINE (PETROLEUM), SWEETENED

Type	Exposure	Value	Population	Effect
DNEL	Oral	19mg/kg/24h	Consumers	Systemic

KEROSINE - UNSPECIFIED - KEROSINE (PETROLEUM), HYDRODESULPHURIZED

Type	Exposure	Value	Population	Effect
DNEL	Oral	19mg/kg/24h	Consumers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Chemically resistant gloves

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

[cont...]

SAFETY DATA SHEET
GUNK ENGINE DEGREASANT SPRAY AEROSOL

Page: 6

Odour: Characteristic odour

Flash point°C: -60

9.2. Other information

Other information: No data available

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
DERMAL	RBT	LD50	<2000	mg/kg
ORAL	RAT	LD50	<5000	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No data available.

[cont...]

SAFETY DATA SHEET
GUNK ENGINE DEGREASANT SPRAY AEROSOL

Page: 7

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

[cont...]

SAFETY DATA SHEET
GUNK ENGINE DEGREASANT SPRAY AEROSOL

Page: 8

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

R12: Extremely flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.