

Revision date 05/09/2024

Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EGR & Carb Cleaner
Product Code(s) HMTN0201B, FAIFPEGR500, NQA2500
Safety data sheet number 000056
Unique Formula Identifier (UFI) 4T40-7098-V00M-FHVK
Pure substance/mixture Mixture

Contains XYLENE-ortho; Acetone; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Car Maintenance Product
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Manufacturer	Supplier
Holts Auto Unit 100 Barton Dock Road Manchester United Kingdom M32 0YQ For further information, please contact	Holt Lloyd Services, 52 Rue des 40 Mines, 60000 – Allonne, France

Contact Point www.holtsauto.com

E-mail address info@holtsauto.com

1.4. Emergency telephone number

Emergency Telephone Holt Lloyd International: UK - 00 44 (0) 161 866 4800 Office Hours - Mon - Thurs: 8am - 5pm. Fri - 8am - 1pm.
00 44 (0) 161 886 4806 (24 Hour Voicemail).

Emergency Telephone - (EC)1272/2008	
Europe	Europe: 00 44 (0) 161 866 4800 Office Hours - Mon - Thurs: 8am - 5pm. Fri - 8am - 1pm. 00 44 (0) 161 886 4806 (24 Hour Voicemail).
Austria	+43 1 31304 5620; chemikalien@umweltbundesamt.at
Belgium	+3270245245; info@poisoncentre.be
Czech Republic	Toxikologické informační středisko v Praze Na Bojišti 1, 120 00 Praha 2 Tel: +420 224 919 293
France	+33 (0)3 64 99 00 32 Heures de travail - Lundi- Vendredi: 8am- 5pm. (Messagerie vocale 24 heures sur 24)

Hungary	Az Egészségügyi Toxikológiai Tájékoztató Szolgálat elérhetőségei Levelezési cím: 1097 Budapest, Nagyvárad tér 2. (+36-80) 201-199
Ireland	+353 (1) 809 2166 / +353 (1) 809 2566; chemicalsinfo@beaumont.ie
Slovakia	Národné toxikologické informačné centrum, Klinika pracovného lekárstva a toxikológie LF UK, Limbová 5, 833 05 Bratislava. Tel.: 02/5477 4166.
United Kingdom	Holt Lloyd International: UK - 00 44 (0) 161 866 4800 Office Hours - Mon - Thurs: 8am - 5pm. Fri - 8am - 1pm. 00 44 (0) 161 886 4806 (24 Hour Voicemail).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosols	Category 1 - (H222, H229)
Acute toxicity - Inhalation (Gases)	Category 4 - (H332)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity — single exposure	Category 3 - (H335, H336)
Hazardous to the aquatic environment - chronic	Category 2 - (H411)

2.2. Label elements

Contains XYLENE-ortho; Acetone; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane



Signal word

Danger

Hazard statements

H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects
EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, eye protection and face protection.
P391 - Collect spillage.
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/ container to an approved waste disposal plant.

Labelling for contents according to regulation (EC) No. 648/2004

Aliphatic hydrocarbons	>= 30%
------------------------	--------

- 0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
- 0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
- 0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
- 0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapour).
- 0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Unknown aquatic toxicity Contains 0 % of components with unknown hazards to the aquatic environment.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

No information available.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
XYLENE-ortho 95-47-6	25 - <50%	No data available	202-422-2 (601-022-00-9)	Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Flam. Liq. 3 (H226) Aquatic Chronic 3 (H412) Eye Irrit. 2 (H319) STOT SE 3 (H335) Asp. Tox. 1 (H304)	-	-	-
Acetone 67-64-1	10 - <25%	01-2119471330-49-00 00	200-662-2 (606-001-00-8)	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane -	5 - <10%	No data available	-	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aquatic Chronic 2 (H411)	-	9	-

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
XYLENE-ortho 95-47-6	3608	14100	No data available	23.0258	No data available
Acetone 67-64-1	5800	15700	100.2	No data available	No data available

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur. If symptoms persist, call a doctor. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists. Use personal protective equipment as required. See section 8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing. Difficulty in breathing.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid breathing vapours or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment.

Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Keep out of the reach of children.

Storage class (TRGS 510) LGK 2B.

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
XYLENE-ortho 95-47-6	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ *	TWA: 50 ppm TWA: 221 mg/m ³ STEL 100 ppm STEL 442 mg/m ³	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ D*	STEL: 100 ppm STEL: 442.0 mg/m ³ TWA: 50 ppm TWA: 221.0 mg/m ³ K*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ *
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³ STEL 2000 ppm STEL 4800 mg/m ³	TWA: 246 ppm TWA: 594 mg/m ³ STEL: 492 ppm STEL: 1187 mg/m ³	STEL: 1400 mg/m ³ TWA: 600 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³
Chemical name	Cyprus	Czech Republic	Denmark	Estonia	Finland
XYLENE-ortho 95-47-6	* STEL: 100 ppm STEL: 442 mg/m ³ TWA: 50 ppm TWA: 221 mg/m ³	TWA: 200 mg/m ³ Ceiling: 400 mg/m ³ D*	TWA: 25 ppm TWA: 109 mg/m ³ H* STEL: 442 mg/m ³ STEL: 100 ppm	TWA: 50 ppm TWA: 200 mg/m ³ STEL: 100 ppm STEL: 450 mg/m ³ A*	TWA: 50 ppm TWA: 220 mg/m ³ STEL: 100 ppm STEL: 440 mg/m ³ iho*
Acetone 67-64-1	* TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 800 mg/m ³ Ceiling: 1500 mg/m ³	TWA: 250 ppm TWA: 600 mg/m ³ STEL: 500 ppm STEL: 1200 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 630 ppm STEL: 1500 mg/m ³
Chemical name	France	Germany TRGS	Germany DFG	Greece	Hungary
XYLENE-ortho 95-47-6	TWA: 50 ppm TWA: 221 mg/m ³	TWA: 50 ppm TWA: 220 mg/m ³	TWA: 50 ppm TWA: 220 mg/m ³	TWA: 100 ppm TWA: 435 mg/m ³	TWA: 221 mg/m ³ TWA: 50 ppm

	STEL: 100 ppm STEL: 442 mg/m ³ *	H*	Peak: 100 ppm Peak: 440 mg/m ³ *	STEL: 150 ppm STEL: 650 mg/m ³ *	STEL: 100 ppm STEL: 442 mg/m ³ b*
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1000 ppm STEL: 2420 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³ Peak: 1000 ppm Peak: 2400 mg/m ³	TWA: 1780 mg/m ³ STEL: 3560 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³
Chemical name	Ireland	Italy MDLPS	Italy AIDII	Latvia	Lithuania
XYLENE-ortho 95-47-6	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ Sk*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ cute*	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ Ada*	O* TWA: 221 mg/m ³ TWA: 50 ppm STEL: 442 mg/m ³ STEL: 100 ppm
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3630 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 250 ppm TWA: 594 mg/m ³ STEL: 500 ppm STEL: 1187 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1000 ppm STEL: 2420 mg/m ³
Chemical name	Luxembourg	Malta	Netherlands	Norway	Poland
XYLENE-ortho 95-47-6	Peau* STEL: 100 ppm STEL: 442 mg/m ³ TWA: 50 ppm TWA: 221 mg/m ³	skin* STEL: 100 ppm STEL: 442 mg/m ³ TWA: 50 ppm TWA: 221 mg/m ³	TWA: 47.5 ppm TWA: 210 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ H*	TWA: 25 ppm TWA: 108 mg/m ³ STEL: 37.5 ppm STEL: 135 mg/m ³ H*	STEL: 200 mg/m ³ TWA: 100 mg/m ³ skóra*
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1 ppm STEL: 2420 mg/m ³	TWA: 125 ppm TWA: 295 mg/m ³ STEL: 156.25 ppm STEL: 368.75 mg/m ³	STEL: 1800 mg/m ³ TWA: 600 mg/m ³
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
XYLENE-ortho 95-47-6	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ Cutânea*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ P*	TWA: 50 ppm TWA: 221 mg/m ³ K* Ceiling: 442 mg/m ³	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ K*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ vía dérmica*
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 750 ppm	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 2420 mg/m ³ STEL: 1000 ppm	TWA: 500 ppm TWA: 1210 mg/m ³
Chemical name	Sweden		Switzerland	United Kingdom	
XYLENE-ortho 95-47-6	NGV: 50 ppm NGV: 221 mg/m ³ Bindande KGV: 100 ppm Bindande KGV: 442 mg/m ³ H*		TWA: 50 ppm TWA: 220 mg/m ³ STEL: 100 ppm STEL: 440 mg/m ³ H*	TWA: 50 ppm TWA: 220 mg/m ³ STEL: 100 ppm STEL: 441 mg/m ³ Sk*	
Acetone 67-64-1	NGV: 250 ppm NGV: 600 mg/m ³ Vägledande KGV: 500 ppm Vägledande KGV: 1200 mg/m ³		TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 1000 ppm STEL: 2400 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³	

**Biological occupational exposure
limits**

Chemical name	European Union	Austria	Bulgaria	Croatia	Czech Republic
XYLENE-ortho 95-47-6	-	1.5 g/L (urine - Methylhippuric acid after end of work day, at the end of a work week/end of the shift)	-	1.50 mg/L - blood (Xylene) - at the end of the work shift 1.50 g/g Creatinine - urine (Methylhippuric acid) - at the end of the work shift	-

Acetone 67-64-1	-	-	80 mg/L - urine (Acetone) - at the end of exposure or end of work shift	20.0 mg/L - blood (Acetone) - at the end of the work shift 20.0 mg/g Creatinine - urine (Acetone) - at the end of the work shift	-
Chemical name	Denmark	Finland	France	Germany DFG	Germany TRGS
XYLENE-ortho 95-47-6	-	-	- urine (Methylhippuric acid) - end of shift	2000 mg/L (urine - Methylhippuric(tolur-)acid (all isomers) end of shift) 2000 mg/L - BAT (end of exposure or end of shift) urine	2000 mg/L (urine - Methylhippuric(tolur-)acid (all isomers) end of shift)
Acetone 67-64-1	-	-	- urine (Acetone) - end of shift	50 mg/L (urine - Acetone end of shift) 50 mg/L - BAT (end of exposure or end of shift) urine 2.5 mg/L - BAR (end of exposure or end of shift) urine	50 mg/L (urine - Acetone end of shift)
Chemical name	Hungary	Ireland	Italy MDLPS	Italy AIDII	
XYLENE-ortho 95-47-6	1500 mg/g Creatinine (urine - Methyl hippuric acid end of shift) 860 µmol/mmol Creatinine (urine - Methyl hippuric acid end of shift)	1.5 g/g Creatinine (urine - Methylhippuric acids end of shift)	-	1.5 g/g Creatinine - urine (Methylhippuric acids) - end of shift	
Acetone 67-64-1	-	50 mg/L (urine - Acetone end of shift)	-	25 mg/L - urine (Acetone) - end of shift	
Chemical name	Latvia	Luxembourg	Romania	Slovakia	
XYLENE-ortho 95-47-6	-	-	3 g/L - urine (Methylhippuric acid) - end of shift	-	
Acetone 67-64-1	-	-	50 mg/L - urine (Acetone) - end of shift	80 mg/L (urine - Acetone end of exposure or work shift)	
Chemical name	Slovenia	Spain	Switzerland	United Kingdom	
XYLENE-ortho 95-47-6	2 g/L - urine (Methylhippuric acid (all isomers)) - at the end of the work shift	-	-	650 mmol/mol creatinine - urine (Methyl hippuric acid) - post shift	
Acetone 67-64-1	80.0 mg/L - urine (Acetone) - at the end of the work shift	50 mg/L (urine - Acetone end of shift)	50 mg/L (urine - Acetone end of shift) 0.86 mmol/L (urine - Acetone end of shift)	-	

Derived No Effect Level (DNEL) - Workers

Chemical name	Oral	Dermal	Inhalation
Acetone 67-64-1	-	186 mg/kg bw/day [4] [6]	1210 mg/m ³ [4] [6] 2420 mg/m ³ [5] [7]

Notes

[4]

Systemic health effects.

- [5] Local health effects.
- [6] Long term.
- [7] Short term.

Derived No Effect Level (DNEL) - General Public

Chemical name	Oral	Dermal	Inhalation
Acetone 67-64-1	62 mg/kg bw/day [4] [6]	-	200 mg/m ³ [4] [6]

Notes

- [4] Systemic health effects.
- [6] Long term.

Predicted No Effect Concentration (PNEC)

Chemical name	Freshwater	Freshwater (intermittent release)	Marine water	Marine water (intermittent release)	Air
Acetone 67-64-1	10.6 mg/L	21 mg/L	1.06 mg/L	-	-

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
Acetone 67-64-1	30.4 mg/kg sediment dw	3.04 mg/kg sediment dw	100 mg/L	29.5 mg/kg soil dw	-

8.2. Exposure controls

Engineering controls No information available.

Personal protective equipment

Eye/face protection Tight sealing safety goggles. Safety glasses with side shields are recommended for medical or industrial exposures.

Hand protection Impervious gloves. Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Aerosol
Appearance	Aerosol
Colour	Colourless
Odour	Aromatic hydrocarbons.
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available - °C	sds.support@halfords.co.uk
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available °C	Closed cup
Autoignition temperature	200 °C	sds.support@halfords.co.uk
Decomposition temperature		None known
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	0.825 @ 20°C	None known
Bulk density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

VOC content 95.89%

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	8,539.60 mg/kg
ATEmix (dermal)	33,372.80 mg/kg
ATEmix (inhalation-gas)	10,650.90 ppm
ATEmix (inhalation-vapour)	54.50 mg/l
ATEmix (inhalation-dust/mist)	3.55 mg/l

0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapour).
0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
XYLENE-ortho	= 3608 mg/kg (Rat)	= 14100 mg/kg (Rabbit)	= 4330 ppm (Rat) 6 h
Acetone	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation No information available.

Germ cell mutagenicity No information available.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
XYLENE-ortho	Muta. 1B

Carcinogenicity No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
XYLENE-ortho	Carc. 1B

Reproductive toxicity No information available.

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Unknown aquatic toxicity Contains 0 % of components with unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
XYLENE-ortho	EC50: =4.7mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 11.6 - 22.4mg/L (96h, Pimephales promelas) LC50: 11.6 - 22.4mg/L (96h, Lepomis macrochirus) LC50: 5.59 - 11.6mg/L (96h, Oncorhynchus mykiss) LC50: =12mg/L (96h, Poecilia reticulata)	-	EC50: =3.2mg/L (48h, Daphnia magna) EC50: 2.61 - 5.59mg/L (48h, Daphnia magna) EC50: 0.78 - 2.51mg/L (48h, Daphnia magna)
Acetone	-	LC50: 4.74 - 6.33mL/L (96h, Oncorhynchus mykiss) LC50: 6210 - 8120mg/L (96h, Pimephales promelas) LC50: =8300mg/L (96h, Lepomis macrochirus)	-	EC50: 10294 - 17704mg/L (48h, Daphnia magna) EC50: 12600 - 12700mg/L (48h, Daphnia magna)

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
XYLENE-ortho	3.12
Acetone	-0.24

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
XYLENE-ortho	The substance is not PBT / vPvB
Acetone	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	None
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	190, 327, 344, 625

IMDG

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	AEROSOLS, FLAMMABLE
14.3 Transport hazard class(es)	2.1
14.4 Packing group	None
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	None
EmS-No.	F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments	No information available

RID

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	AEROSOL, FLAMMABLE
14.3 Transport hazard class(es)	2.1
14.4 Packing group	None
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	None

ADR

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	AEROSOLS, FLAMMABLE
14.3 Transport hazard class(es)	2.1
14.4 Packing group	None
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	None
Tunnel restriction code	(D)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
XYLENE-ortho - 95-47-6	RG 4bis, RG 84
Acetone - 67-64-1	RG 84

Germany

Water hazard class (WGK) obviously hazardous to water (WGK 2)

Netherlands

Chemical name	Netherlands - List of Carcinogens	Netherlands - List of Mutagens	Netherlands - List of Reproductive Toxins
XYLENE-ortho	-	-	Development Category 2

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorisations and/or restrictions on use:

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorisation per REACH Annex XIV
XYLENE-ortho - 95-47-6	Use restricted. See entry 75.	-
Acetone - 67-64-1	Use restricted. See entry 75.	-

Persistent Organic Pollutants

Not applicable

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

P3b - FLAMMABLE AEROSOLS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

International Inventories

TSCA

DSL/NDSL

EINECS/ELINCS

Contact supplier for inventory compliance status

Contact supplier for inventory compliance status

Contact supplier for inventory compliance status

ENCS	Contact supplier for inventory compliance status
IECSC	Contact supplier for inventory compliance status
KECL	Contact supplier for inventory compliance status
PICCS	Contact supplier for inventory compliance status
AIIC	Contact supplier for inventory compliance status
NZIoC	Contact supplier for inventory compliance status

Legend:

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AIIC** - Australian Inventory of Industrial Chemicals
- NZIoC** - New Zealand Inventory of Chemicals

15.2. Chemical safety assessment

Chemical Safety Report No information available

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

- H225 - Highly flammable liquid and vapour
- H226 - Flammable liquid and vapour
- H304 - May be fatal if swallowed and enters airways
- H312 - Harmful in contact with skin
- H315 - Causes skin irritation
- H319 - Causes serious eye irritation
- H332 - Harmful if inhaled
- H335 - May cause respiratory irritation
- H336 - May cause drowsiness or dizziness
- H411 - Toxic to aquatic life with long lasting effects
- H412 - Harmful to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitisers		

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method

Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
 U.S. Environmental Protection Agency ChemView Database
 European Food Safety Authority (EFSA)
 European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
 European Chemicals Agency (ECHA) (ECHA_API)
 EPA (Environmental Protection Agency)
 Acute Exposure Guideline Level(s) (AEGL(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 National Institute of Technology and Evaluation (NITE)
 Australian National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
 Organisation for Economic Co-operation and Development Screening Information Data Set
 World Health Organization

Revision date 05/09/2024

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet