

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 1 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name: Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Product code: 8265, 8265S, 8265H, 80165, 8280, 8281, 8272



1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Not determined or not applicable.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

1.3 Details of the manufacturer/supplier of the safety data sheet

Manufacturer:

North America

JB Weld Company, LLC
400 CMH Road
Sulphur Springs, TX 75482
903-885-7696
info@jbweld.com

Supplier:

European Union

JRP Distribution Ltd.
Unit 3 New Wharf Brighton Road
Shoreham by Sea, BN43 6RN

1.4 Emergency telephone number:

United Kingdom

CHEMTREC

1-703-527-3887

+(44)-870-8200418 (London)

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture:

Classification according to Regulation (EC) No. 1272/2008 (CLP):

Serious eye damage, category 1

Skin corrosion, category 1C

Skin sensitization, category 1

Specific target organ toxicity - repeated exposure, category 2

Chronic aquatic hazard, category 3

Hazard-determining components of labeling:

Fatty acids, tall-oil, reaction products with tetraethylenepentamine

Copolymer of benzenamine and formaldehyde, hydrogenated

Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines

2.2 Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H318 Causes serious eye damage.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 2 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash skin thoroughly after handling.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P310 Immediately call a POISON CENTER or doctor/physician.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 Specific treatment (see supplemental first aid instructions on this label).
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention
P362+P364 Take off contaminated clothing and wash it before reuse.
P314 Get medical advice/attention if you feel unwell
P405 Store locked up.
P501 Dispose of contents and container in accordance with local regulations.

2.3 Other hazards: None known

SECTION 3: Composition/information on ingredients

3.1 Substance: Not applicable.

3.2 Mixture:

Identification	Name	Classification according to Regulation (EC) No. 1272/2008 (CLP)	Weight %
CAS number: 37244-96-5	Nepheline syenite	Not classified	35-40
CAS number: 7727-43-7 EC number: 231-784-4	Barium Sulfate, Natural	Not classified	20-25
CAS number: 68410-23-1	Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	Skin Irrit. 2 ; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 2; H411	10-15
CAS number: 135108-88-2	Copolymer of benzenamine and formaldehyde, hydrogenated	Acute Tox. 4; H302 Skin Sens. 1; H317 Skin Corr. 1C; H314 Stot RE 2; H373 Aquatic Chronic 3; H412	5-10
CAS number: 68953-36-6 EC number: 273-201-6	Fatty acids, tall-oil, reaction products with tetraethylenepentamine	Not classified	5-10
CAS number: 14807-96-6 EC number: 238-877-9	Talc	Not classified	1-5

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 3 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

CAS number: 65997-17-3 EC number: 266-046-0	Glass, oxide, chemicals	Not classified	2
CAS number: 13463-67-7 EC number: 236-675-5	Titanium Dioxide	Not classified	<2
CAS number: 90-72-2 EC number: 202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	Acute Tox. 4; H302 Skin Irrit. 2 ; H315 Eye Irrit. 2; H319	<2
CAS number: 1302-78-9 EC number: 215-108-5	Bentonite	Not classified	<2
CAS number: 112-57-2 EC number: 203-986-2	1,2-Ethanediamine, N1-(2-aminoethyl)-N2-[2-[(2-aminoethyl)amino]ethyl]-	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Sens. 1; H317 Skin Corr. 1B; H314 Aquatic Chronic 2; H411	<1
CAS number: 100-51-6 EC number: 202-859-9	Benzyl Alcohol	Acute Tox. 4; H302 Acute Tox. 4; H332	<1
CAS number: 112-24-3 EC number: 203-950-6	Triethylenetetramine	Acute Tox. 4; H312 Skin Sens. 1; H317 Skin Corr. 1B; H314 Aquatic Chronic 3; H412	<1
CAS number: 67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica	Not classified	<1
CAS number: 71074-89-0 EC number: 275-162-0	Bis[(dimethylamino)methyl]phenol	Skin Corr. 1B; H314	<1

Additional information:

Fiberglass powder (CAS # 65997-17-3) is classified as a carcinogen in its inhalable form. Since the fiberglass powder in this product is not inhalable, the product itself is not classified as a carcinogen in the form presented.

Full Text of H and EUH statements: See section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes:

Not determined or not available.

Following inhalation:

- Loosen clothing as necessary and position individual in a comfortable position
- Maintain an unobstructed airway
- Get medical advice/attention if you feel unwell
- Take precautions to ensure your own safety
- Remove source of exposure or move person to fresh air and keep comfortable for breathing
- Immediately call a POISON CONTROL CENTER or seek medical attention
- If breathing has stopped, trained personnel should begin rescue breathing
- Avoid mouth-to-mouth contact by using a barrier device

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 4 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

If the heart has stopped, immediately start cardiopulmonary resuscitation (CPR)

Following skin contact:

Rinse affected area with soap and water
If symptoms develop or persist, seek medical attention
Avoid direct contact and wear chemical protective clothing, if necessary
Immediately take off all contaminated clothing
Gently blot or brush away excess product
Rinse skin with lukewarm, gently flowing water until medical aid is available
Immediately call a POISON CONTROL CENTER or seek medical attention
Wash contaminated clothing before re-use or discard

Following eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes
If symptoms develop or persist, seek medical attention
Avoid direct contact and wear chemical protective gloves, if necessary
Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open
Remove contact lenses, if present and easy to do so
Continue rinsing until medical aid is available
Immediately call a POISON CONTROL CENTER or seek medical attention

Following ingestion:

Rinse mouth thoroughly
Seek medical attention if irritation, discomfort, or vomiting persists
Immediately call a POISON CONTROL CENTER or seek medical attention
Do not induce vomiting and rinse mouth
If vomiting occurs naturally, lie on your side, in the recovery position
If breathing has stopped, trained personnel should begin rescue breathing
Avoid mouth-to-mouth contact by using a barrier device
If the heart has stopped, immediately start cardiopulmonary resuscitation (CPR)

4.2 Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not available.

Delayed symptoms and effects:

Not determined or not available.

4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment:

Not determined or not available.

Notes for the doctor:

Not determined or not available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition.

Unsuitable extinguishing media:

Not determined or not applicable.

5.2 Special hazards arising from the substance or mixture:

Thermal decomposition can lead to release of irritating gases and vapors.

5.3 Advice for firefighters

Personal protection equipment:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit.

Special precautions:

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 5 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Not determined or not applicable.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.
Ensure air handling systems are operational.
Wear protective eye wear, gloves and clothing.

6.2 Environmental precautions:

Should not be released into the environment.
Prevent from reaching drains, sewer or waterway.

6.3 Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing.
Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders).
Dispose of contents / container in accordance with local regulations.

6.4 Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Use only with adequate ventilation.
Avoid breathing mist or vapor.
Do not eat, drink, smoke or use personal products when handling chemical substances.

7.2 Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.
Protect from freezing and physical damage.
Store in a cool, well-ventilated area.

7.3 Specific end use(s):

Not determined or not applicable.

SECTION 8: Exposure controls/personal protection



8.1 Control parameters

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Bulgaria	Benzyl Alcohol	100-51-6	TWA: 5.0 mg/m ³
	Glass, oxide, chemicals	65997-17-3	TWA: 6.0 mg/m ³ (inhalable fraction)
	Bentonite	1302-78-9	TWA: 6.0 mg/m ³ (inhalable fraction)
	Glass, oxide, chemicals	65997-17-3	TWA: 1.0 fibres/cm ³ (respirable fraction)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 6 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Bentonite	1302-78-9	TWA: 3.0 mg/m ³ (respirable fraction)
	Barium Sulfate, Natural	7727-43-7	TWA 8-hr: 10 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Respirable dust)
	Talc	14807-96-6	TWA: 6.0 mg/m ³ (inhalable fraction)
	Talc	14807-96-6	TWA: 3.0 mg/m ³ (respirable fraction)
Estonia	Triethylenetetramine	112-24-3	8-hour TWA: 1 ppm (6 mg/m ³)
	Triethylenetetramine	112-24-3	STEL: 12 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 5 mg/m ³ 8-hr
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 1 fibers/cm ³
	Talc	14807-96-6	8-hour TWA: 10 mg/m ³ (total dust)
	Talc	14807-96-6	8-hour TWA: 5 mg/m ³ (fine dust)
	Talc	14807-96-6	8-hour TWA: 3 mg/m ³ (plastic)
	Talc	14807-96-6	8-hour TWA: 1 mg/m ³ (textile)
	Talc	14807-96-6	8-hour TWA: 5 mg/m ³ (organic dust, total dust)
Czech Republic	Benzyl Alcohol	100-51-6	8-hour TWA: 40 mg/m ³
	Benzyl Alcohol	100-51-6	Ceiling limit (NPK-P): 80 mg/m ³
	Bentonite	1302-78-9	8-hour TWA: 6.0 mg/m ³
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 5.0 mg/m ³ (glass laminate dusts)
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 1.0 fibers/cm ³ (respirable fibers)
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 4 mg/m ³ (synthetic mineral fibers - all sizes)
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 1.0 fibers/cm ³ (synthetic mineral respirable fibers)
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 0.3 fibers/cm ³ (ceramic respirable fibers)
	Talc	14807-96-6	8-hour TWA: 2.0 mg/m ³ (dust, respirable fraction, Fr ≤ 5%)
	Talc	14807-96-6	8-hour TWA: 10 mg/m ³ (dust, respirable fraction, Fr > 5%)
	Talc	14807-96-6	8-hour TWA: 10 mg/m ³ (dust, total concentration)
	Talc	14807-96-6	8-hour TWA: 5.0 mg/m ³ (polymeric material dust)
Lithuania	Triethylenetetramine	112-24-3	8-hour TWA: 6 mg/m ³ (1 ppm)
	Triethylenetetramine	112-24-3	15-minute STEL: 12 mg/m ³ (2 ppm)
	Benzyl Alcohol	100-51-6	8-hour TWA: 5 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 5 mg/m ³ 8-hr
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 1 fibers/cm ³ (glass fiber)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 7 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 0.2 fibers/cm ³ (synthetic inorganic, crystal fibers)
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 1 fibers/cm ³ (synthetic inorganic, amorphous fibers)
	Talc	14807-96-6	8-hour TWA: 2 mg/m ³ (inhalable fraction)
	Talc	14807-96-6	8-hour TWA: 1 mg/m ³ (respirable fraction)
Latvia	Benzyl Alcohol	100-51-6	8-hour TWA: 5 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 2 mg/m ³
	Talc	14807-96-6	8-hour TWA: 4 mg/m ³ (tuff, pumice, perlite)
	Talc	14807-96-6	8-hour TWA: 2 mg/m ³ (natural and synthetic)
	Talc	14807-96-6	8-hour TWA: 5 mg/m ³ (polymers)
	Talc	14807-96-6	8-hour TWA: 2 mg/m ³ (abrasive dusts)
	Talc	14807-96-6	8-hour TWA: 4 mg/m ³ (tal-like dust)
Poland	Triethylenetetramine	112-24-3	8-hour TWA (NDS): 1 mg/m ³
	Benzyl Alcohol	100-51-6	8-hour TWA (NDS): 240 mg/m ³
	Triethylenetetramine	112-24-3	15-minute STEL (NDSch): 3 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA (NDS) 10.0 mg/m ³ 8-hr
	Glass, oxide, chemicals	65997-17-3	8-hour TWA(NDS): 2.0 mg/m ³ (inhalable fraction)
	Glass, oxide, chemicals	65997-17-3	8-hour TWA (NDS): 1.0 fibers/cm ³ (respirable fibers)
	Talc	14807-96-6	8-hour TWA (NDS): 4 mg/m ³ (inhalable fraction)
	Talc	14807-96-6	8-hour TWA (NDS): 1 mg/m ³ (respirable fraction)
Cyprus	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 10 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Talc	14807-96-6	8-hour TWA: 706 particles/cm ³
Finland	Benzyl Alcohol	100-51-6	8-hour limit: 10 ppm (45 mg/m ³)
	Barium Sulfate, Natural	7727-43-7	TWA 8-hr: 10 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Glass, oxide, chemicals	65997-17-3	8-hour limit: 5 mg/m ³
	Talc	14807-96-6	15-minute limit: 2 ppm (inhalable)
	Talc	14807-96-6	15-minute limit: 1 ppm (respirable)
Slovakia	Bentonite	1302-78-9	8-hour TWA (NPEL): 6 mg/m ³
	Barium Sulfate, Natural	7727-43-7	NPEL TWA 8-hr: 4 mg/m ³ (Inhalable fraction), 1.5 mg/m ³ (Respirable fraction)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 8 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Titanium Dioxide	13463-67-7	OEL: TWA (NPEL) 5 mg/m ³ 8-hr
	Glass, oxide, chemicals	65997-17-3	8-hour TWA (NPEL): 2 fibers/cm ³ (4 mg/m ³)
	Talc	14807-96-6	8-hour TWA (NPEL): 2 mg/m ³ (respirable fraction, Fr ≤ 5%)
	Talc	14807-96-6	8-hour TWA: 2 mg/m ³ (respirable fraction, Fr > 5 %)
Romania	Triethylenetetramine	112-24-3	8-hour TWA: 10 mg/m ³ (1.7 ppm)
	Triethylenetetramine	112-24-3	15-minute STEL: 20 mg/m ³ (3.3 ppm)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Titanium Dioxide	13463-67-7	OEL: STEL 15 mg/m ³ 15-min
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 1 fibers/cm ³ (glass wool fibers - respirable fraction)
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 1 fibers/cm ³ (rock wool fibers - respirable fraction)
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 1 fibers/cm ³ (slag wool fibers - respirable fraction)
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 1 fibers/cm ³ (special purpose glass fibers - respirable fraction)
	Talc	14807-96-6	8-hour TWA: 2 mg/m ³ (inhalable fraction)
Croatia	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Total dust) 15-min
	Barium Sulfate, Natural	7727-43-7	TWA 8-hr: 10 mg/m ³ (Total dust); 4 mg/m ³ (Respirable dust)
	Titanium Dioxide	13463-67-7	OEL: TWA 4.0 mg/m ³ (Respirable dust) 15-min
	Talc	14807-96-6	Maximum (8 hr) allowable concentration: 1 mg/m ³ (respirable dust)
Sweden	Triethylenetetramine	112-24-3	Level Limit Value (NGV): 1 ppm (6 mg/m ³)
	Triethylenetetramine	112-24-3	Short Term Limit (KTV): 2 ppm (12 mg/m ³)
	Titanium Dioxide	13463-67-7	OEL: (NGV) 5.0 (Total dust) mg/m ³
	Glass, oxide, chemicals	65997-17-3	Level Limit Value (NGV): 1 fiber/mL
	Talc	14807-96-6	Level Limit Value (NGV): 2 mg/m ³ (total dust)
	Talc	14807-96-6	Level Limit Value (NGV): 1 mg/m ³ (respirable dust)
Belgium	Barium Sulfate, Natural	7727-43-7	TWA 8-hr: 10 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 10 mg/m ³ (glass - fibers or dusts of)
	Talc	14807-96-6	8-hour TWA: 2 mg/m ³
	Talc	14807-96-6	8-hour TWA: 10 mg/m ³ (inhalable fraction)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 9 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Talc	14807-96-6	8-hour TWA: 3 mg/m ³ (respirable fraction)
Hungary	Glass, oxide, chemicals	65997-17-3	8-Hour TWA (ÁK Value): 1.0 fibers/cm ³
	Talc	14807-96-6	8-hour TWA (ÁK Value): 2 mg/m ³ (respirable)
	Talc	14807-96-6	8-hour TWA (ÁK Value): 10 mg/m ³ (total, inhalable)
Ireland	Barium Sulfate, Natural	7727-43-7	TWA 8-hr: 2 mg/m ³ (Respirable Dust)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Inhalable dust) 8-hr
	Titanium Dioxide	13463-67-7	OEL: TWA 4.0 mg/m ³ (Respirable dust) 8-hr
	Glass, oxide, chemicals	65997-17-3	8-hour OEL (TWA): 2 fibers/cm ³ of air (5 mg/m ³)
	Talc	14807-96-6	8-hour OEL (TWA): 10 mg/m ³ (total inhalable dust)
	Talc	14807-96-6	8-hour OEL (TWA): 0.8 mg/m ³ (respirable fraction)
Italy	Barium Sulfate, Natural	7727-43-7	TWA 8-hr: 5 mg/m ³ (Inhalable fraction)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 1 fibres/cm ³
	Talc	14807-96-6	8-hour TWA: 2 mg/m ³ (respirable fraction)
Portugal	Barium Sulfate, Natural	7727-43-7	TWA 8-hr: 10 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Glass, oxide, chemicals	65997-17-3	NP 1796-2007 8-hour exposure limit: 1 fibres/cm ³
	Talc	14807-96-6	NP 1796-2007 8-hour exposure limit: 2 mg/m ³ (respirable fraction)
Spain	Barium Sulfate, Natural	7727-43-7	VLA-ED 8-hr: 10 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: (VLA_ED) 10.0 mg/m ³ 8-hr
	Glass, oxide, chemicals	65997-17-3	8-hour daily exposure limit (VLA_ED): 0.5 fibres/cm ³
	Talc	14807-96-6	8-hour daily exposure limit (VLA_ED): 2 mg/m ³ (respirable fraction)
United Kingdom	Barium Sulfate, Natural	7727-43-7	TWA: 10 mg/m ³ (Inhalable dust), 4 mg/m ³ (Respirable dust)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Total dust)
	Titanium Dioxide	13463-67-7	OEL: TWA 4.0 mg/m ³ (Respirable dust)
	Glass, oxide, chemicals	65997-17-3	TWA: 1 fibre/mL (5 mg/m ³)
	Talc	14807-96-6	TWA: 1 mg/m ³ (respirable dust)
Austria	Titanium Dioxide	13463-67-7	OEL: TWA 5 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: STEL 10 mg/m ³

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 10 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Denmark	Titanium Dioxide	13463-67-7	OEL: TWA 6.0 mg/m ³
	Glass, oxide, chemicals	65997-17-3	TWA: 1 fibers/cm ³
France	Titanium Dioxide	13463-67-7	OEL: (VME) 10 mg/m ³
	Talc	14807-96-6	Time weighted average (VME): 10 mg/m ³ (inhalable fraction)
	Talc	14807-96-6	Time weighted average (VME): 5 mg/m ³ (respirable fraction)
Slovenia	Glass, oxide, chemicals	65997-17-3	8-hour TWA: 500000 fibers/m ³
	Talc	14807-96-6	8-hour TWA: 2 mg/m ³ (Respirable fraction)
Greece	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Inhalable) 8-hr
	Titanium Dioxide	13463-67-7	OEL: TWA 5.0 mg/m ³ (Respirable dust) 8-hr
	Talc	14807-96-6	8-hour TWA: 10 mg/m ³ (inhalable)
	Talc	14807-96-6	8-hour TWA: 2 mg/m ³ (respirable)
Netherlands	Glass, oxide, chemicals	65997-17-3	Binding 8-hour TWA: 0.5 fibre/cm ³
	Talc	14807-96-6	8-hour TWA: 0.25 mg/m ³ (respirable)
Germany	Talc	14807-96-6	AGW Limit value: 1.25 mg/m ³ (respirable fraction)
	Talc	14807-96-6	AGW limit value: 10 mg/m ³ (inhalable fraction)
	Talc	14807-96-6	AGW Short term (15 min) exposure limit: 20 mg/m ³ (inhalable fraction)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Derived No Effect Level (DNEL):

Not determined or not applicable.

Predicted No Effect Concentration (PNEC):

Not determined or not applicable.

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls
Biological monitoring may also be appropriate for some substances

8.2 Exposure controls

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 11 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Skin and body protection:

Select glove material impermeable and resistant to the substance.
Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.
Wash hands before breaks and at the end of work.
Wash contaminated clothing before reuse.

Environmental exposure controls:

Select controls based on a risk assessment of local conditions.
See section 6 for information on accidental release measures.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	White liquid
Odor	Amine-like
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Closed cup: >93.3 °C (>199.9 °F) [Setaflash.] [Product does not sustain combustion.]
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	1.955
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	>220°C (>392°F)
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

9.2 Other information

VOC Content	<1%
-------------	-----

SECTION 10: Stability and reactivity

10.1 Reactivity:

Does not react under normal conditions of use and storage.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 12 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

10.2 Chemical stability:

Stable under normal conditions of use and storage.

10.3 Possibility of hazardous reactions:

None under normal conditions of use and storage.

10.4 Conditions to avoid:

None known.

10.5 Incompatible materials:

None known.

10.6 Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Benzyl Alcohol	inhalation	LC50 Rat: 4.178 mg/L (4 hr)
	oral	LD50 Rabbit: 1,040 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	oral	LD50 - Rat - 1,200 mg/kg

Skin corrosion/irritation

Assessment: Causes severe skin burns and eye damage

Product data:

No data available.

Substance data:

Name	Result
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	Causes skin irritation.
1,2-Ethanediamine, N1-(2-aminoethyl)-N2-[2-[(2-aminoethyl)amino]ethyl]-	Causes severe skin burns and eye damage.
Copolymer of benzenamine and formaldehyde, hydrogenated	Causes severe skin burns and eye damage.
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	Causes skin irritation.
2,4,6-tris(dimethylaminomethyl)phenol	Causes skin irritation.
Triethylenetetramine	Causes severe skin burns and eye damage.
Bis[(dimethylamino)methyl]phenol	Causes severe skin burns and eye damage.

Serious eye damage/irritation

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 13 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Assessment: Causes serious eye damage

Product data:

No data available.

Substance data:

Name	Result
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	Causes serious eye irritation.
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	Causes serious eye damage.
2,4,6-tris(dimethylaminomethyl)phe nol	Causes serious eye irritation.

Respiratory or skin sensitization

Assessment: May cause an allergic skin reaction

Product data:

No data available.

Substance data:

Name	Result
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	May cause an allergic skin reaction.
Copolymer of benzenamine and formaldehyde, hydrogenated	May cause an allergic skin reaction.
1,2-Ethanediamine, N1-(2-aminoethyl)-N2-[2-[(2-aminoethyl)amino]ethyl]-	May cause an allergic skin reaction.
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	May cause an allergic skin reaction.
Triethylenetetramine	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Glass, oxide, chemicals	Not applicable	May cause cancer via inhalation.
Titanium Dioxide	Not applicable.	Airborne, unbound particles of respirable size are known to cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Glass, oxide, chemicals	Group 2B
Talc	Group 3 - Not classifiable as to its carcinogenicity to humans
Titanium Dioxide	Group 2B

National Toxicology Program (NTP):

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 14 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Name	Classification
Glass, oxide, chemicals	Reasonably anticipated to be human carcinogens

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Assessment: May cause damage to organs through prolonged or repeated exposure

Product data:

No data available.

Substance data:

Name	Result
Copolymer of benzenamine and formaldehyde, hydrogenated	May cause damage to kidneys through prolonged or repeated oral exposure.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 15 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Name	Result
Triethylenetetramine	LC50 - Daphnia magna (Water flea) - 33.9 mg/L - 48 h

Chronic (long-term) toxicity

Product data: No data available.

Substance data:

Name	Result
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	LC50 - Danio rerio - 7.07 mg/L - 96 hr
	EC50 - Daphnia magna - 5.18 mg/L - 48 hr
	ErC50 - Pseudokirchneriella subcapitata - 4.11 mg/L - 72 hr

12.2 Persistence and degradability

Product data: No data available.

Substance data: No data available.

12.3 Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

12.4 Mobility in soil

Product data: No data available.

Substance data: No data available.

12.5 Results of PBT and vPvB assessment

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

12.6 Other adverse effects: No data available.

SECTION 13: Disposal considerations


13.1 Waste treatment methods

Relevant information:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

International Carriage of Dangerous Goods by Road/Rail (ADR/RID)

UN number	UN 1760
UN proper shipping name	Corrosive Liquids, N.O.S., (Copolymer of benzenamine and formaldehyde, hydrogenated, Triethylenetetramine)
UN transport hazard class(es)	8 
Packing group	II
Environmental hazards	None
Special precautions for user	None

International Carriage of Dangerous Goods by Inland Waterways (ADN)

UN number	UN 1760
UN proper shipping name	Corrosive Liquids, N.O.S., (Copolymer of benzenamine and formaldehyde, hydrogenated, Triethylenetetramine)


Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)


Initial preparation date: 01.18.2019

Page 16 of 18


Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

UN transport hazard class(es)	8	
Packing group	II	
Environmental hazards	None	
Special precautions for user	None	

International Maritime Dangerous Goods (IMDG)

UN number	UN 1760	
UN proper shipping name	Corrosive Liquids, N.O.S., (Copolymer of benzenamine and formaldehyde, hydrogenated, Triethylenetetramine)	
UN transport hazard class(es)	8	
Packing group	II	
Environmental hazards	None	
Special precautions for user	None	

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN 1760	
UN proper shipping name	Corrosive Liquids, N.O.S., (Copolymer of benzenamine and formaldehyde, hydrogenated, Triethylenetetramine)	
UN transport hazard class(es)	8	
Packing group	II	
Environmental hazards	None	
Special precautions for user	None	

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

European regulations

Inventory listing (EINECS):

68953-36-6	Fatty acids, tall-oil, reaction products with tetraethylenepentamine	Listed
135108-88-2	Copolymer of benzenamine and formaldehyde, hydrogenated	Not Listed
100-51-6	Benzyl Alcohol	Listed
112-57-2	1,2-Ethanediamine, N1-(2-aminoethyl)-N2-[2-[(2-aminoethyl)amino]ethyl]-	Listed
68410-23-1	Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	Not Listed
112-24-3	Triethylenetetramine	Listed

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 17 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	Listed
71074-89-0	Bis[(dimethylamino)methyl]phenol	Listed
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica	Not Listed
65997-17-3	Glass, oxide, chemicals	Listed
14807-96-6	Talc	Listed
37244-96-5	Nepheline syenite	Not Listed
13463-67-7	Titanium Dioxide	Listed
1302-78-9	Bentonite	Listed
7727-43-7	Barium Sulfate, Natural	Listed

REACH SVHC candidate list: None of the ingredients are listed.

REACH SVHC Authorizations: None of the ingredients are listed.

REACH Restriction: None of the ingredients are listed.

Water hazard class (WGK) (Product): Not determined.

Water hazard class (WGK) (Substance):

Ingredient Name	CAS	Class
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	68953-36-6	2
Benzyl Alcohol	100-51-6	1
1,2-Ethanediamine, N1-(2-aminoethyl)-N2-[2-[(2-aminoethyl)amino]ethyl]-	112-57-2	2
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	68410-23-1	2
Triethylenetetramine	112-24-3	2
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	1
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Non-hazardous to water.
Talc	14807-96-6	Non-hazardous to water.
Titanium Dioxide	13463-67-7	Non-hazardous to water.
Barium Sulfate, Natural	7727-43-7	Non-hazardous to water.

Other regulations

Germany MAK: Talc: 8-hour TWA: 0.3 mg/m³ (respirable fraction), Talc: 8-hour TWA: 4 mg/m³ (inhalable fraction), Benzyl Alcohol: 8-hour TWA: 5 ppm (22 mg/m³), Barium sulfate, Natural: 8-hour TWA: 0.3 mg/m³ (respirable fraction), Barium sulfate, Natural: 8-hour TWA: 4 mg/m³ (inhalable fraction)

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Indication of changes:

Not applicable.

Abbreviations and Acronyms: None

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 18 of 18

Steel Reinforced Epoxy Hardener - Slow Cure - Twin Tube - Part B

Classification procedure:

Classification according to Regulation (EC) No. 1272/2008 (CLP)	Method Used
Serious eye damage, category 1	Calculation method
Skin corrosion, category 1C	Calculation method
Skin sensitization, category 1	Calculation method
Specific target organ toxicity - repeated exposure, category 2	Calculation method
Chronic aquatic hazard, category 3	Calculation method

Summary of classification in section 3:

Skin Irrit. 2 ; H315	Skin irritation, category 2
Eye Dam. 1; H318	Serious eye damage, category 1
Skin Sens. 1; H317	Skin sensitization, category 1
Aquatic Chronic 2; H411	Chronic aquatic hazard, category 2
Acute Tox. 4; H302	Acute toxicity (oral), category 4
Skin Corr. 1C; H314	Skin corrosion, category 1C
Stot RE 2; H373	Specific target organ toxicity - repeated exposure, category 2
Aquatic Chronic 3; H412	Chronic aquatic hazard, category 3
Eye Irrit. 2; H319	Eye irritation, category 2A
Acute Tox. 4; H312	Acute toxicity (dermal), category 4
Skin Corr. 1B; H314	Skin corrosion, category 1B
Acute Tox. 4; H332	Acute toxicity (inhalation), category 4

Summary of hazard statements in section 3:

H315	Causes skin irritation
H318	Causes serious eye damage
H317	May cause an allergic skin reaction
H411	Toxic to aquatic life with long lasting effects
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects
H319	Causes serious eye irritation
H312	Harmful in contact with skin
H332	Harmful if inhaled

Disclaimer:

This product has been classified in accordance with EC No. 1272/2008 (CLP) and EC No. 1907/2006 (REACH). The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 01.18.2019

End of Safety Data Sheet