

Page 1 of 8 Issued: 08/03/2022 Revision No.1 Regulation (EU) No. 453/2010

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product Identifier

Material name : NAPA AIR CON SANITISER 150ML NMS3150

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Cleaning spray

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: NAPA

2, Eskan Court, West Campbell, Milton Keynes MK9 4AN

Tel: +44 (0) 3333 136 597

1.4 Emergency tel no: +44 (0) 3333 136 597 (office hours only)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to 1272/2008/EC: Classification, Labelling and Packaging of Substances and Mixtures (CLP) Regulation:

Physical and Chemical Hazards Flammable Aerosol Category 1; H222; H229

Human health Not classified Environment Not classified.

2.2 Label elements

Labelling according to EC Directives: 1272/2008/EC

Signal word: Danger **Hazard Pictogram(s):**



Hazard Statements: H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary

Statements: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

P261 Avoid breathing vapour/spray.

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/eye/face protection.

P501 Dispose of contents/container in accordance with local/national regulations.

Page 2 of 8 Issued: 13/02/2019; Revision No.1 Regulation (EU) No. 453/2010

2.3 Other hazards In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures:

Hazardous components

Chemical Name	CAS No./ EC No./ Reg. No	Classification (1272/2008/EC)	Content
ETHANOL	64-17-5 200-578-6 01-2119457610-43-xxxx	Flam.Liq.2; H225	70-80%
LIQUEFIED PETROLEUM GAS (contains <0.1% 1,3-butadiene)	68476-85-7 270-704-2	Flam.Gas 1; H220 Gas under pressure; H280	20-25%
PROPAN-2-OL	67-63-0 200-661-7 01-2119457558-25-xxxx	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336	0.1-0.5%

See Section 16 for the full text of the H-statements noted above.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice: Remove casualty from exposure ensuring one's own safety whilst doing so. Take off any contaminated clothing and shoes/boots immediately. Never give anything by mouth to an unconscious person.

Skin contact: Wash with soap and water. Seek medical advice if irritation develops.

 $\textbf{Eye contact}: \ Rinse \ with \ water \ for \ 10 \ minutes \ and \ seek \ immediate \ medical \ attention.$

Ingestion: Rinse mouth with water and give water to drink. Do not induce vomiting. Seek medical advice.

Inhalation: Remove to fresh air. Seek medical advice.

- **4.2 Most important symptoms and effects, both acute and delayed:** May cause eye irritation.
- **4.3 Indication of any immediate medical attention and special treatment needed:** See eye contact information above.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Carbon dioxide; dry chemical powder; alcohol or polymer foam.

Unsuitable extinguishing media: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: Irritating/toxic fumes may be released at elevated temperatures.

Page 3 of 8 Issued: 13/02/2019; Revision No.1 Regulation (EU) No. 453/2010

5.3 Advice for fire-fighters:

Special protective equipment: Wear self-contained breathing apparatus. Use personal protective equipment. Further information: Standard procedure for chemical fires. Use water spray to cool containers.

Do not allow fire run-off to enter drains.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Use personal protective equipment to deal with spillage.

6.2 Environmental precautions

Contain the spillage using sufficient appropriate absorbent material. Do not discharge into drains or rivers, but if contamination to waterways has occurred, inform local authorities.

6.3 Methods and materials for containment and cleaning up

Wipe up liquid spillage with absorbent material such as sand, earth, or vermiculite, and place in a labelled container for disposal in accordance with local/national regulations.

6.4 References to other sections: See sections 8 and 13 for personal protection and disposal information.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Do not breathe spray mist. Avoid contact with skin and eyes. Handle with care.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, well ventilated area, below 50°C. Protect from frost, heat and sunlight. Keep away from food, drink and animal feed.

7.3 Specific end use(s): No information available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Chemical name	8hr TWA	15min STEL	Reference
Ethanol	1920 mg/m ³ /1000ppm	-	EH40/2005
Liquefied petroleum gas	1750 mg/m ³ /1000ppm	2810 mg/m ³ /1250 ppm	EH40/2005

DNEL/PNEC: No information available.

8.2 Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Personal protective equipment

Respiratory protection: Unlikely to be necessary in normal circumstances; if vapour levels are high, wear a respirator conforming to EN 140 fitted with an organic vapour filter.

Page 4 of 8 Issued: 13/02/2019; Revision No.1 Regulation (EU) No. 453/2010

Hand protection: Wear chemically resistant gloves such as butyl rubber approved to standard EN 374; material thickness 0.5mm; break through time ≥ 480 min. Gloves must be replaced after 8 hours of wear. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Check with glove manufacturer for specific advice.

Eye protection: Chemical splash goggles if eye contact is reasonably probable. The selected goggles or glasses must satisfy the European standard EN 166.

Skin and body protection: Protective overalls.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practices. Do not eat or drink whilst using the product. Wash hands before breaks and at the end of the work day. Wash contaminated clothing before re-use.

Environmental exposure controls: Do not discharge into drains or rivers.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

State and colour Aerosol emitting colourless spray.

 $<0^{\circ}C$

Fragranced Odour **Odour Threshold** No data available **Flammability** Extremely flammable

Flash point Lower explosion limit 0.8% Upper explosion limit 12.0% **Explosive properties** Not explosive Thermal decomposition No data available **Auto-ignition temperature** No data available **Oxidising properties** Non-oxidising Solubility in water Miscible

Solubility in other solvents Miscible with alcohols pН No data available Melting point/range No data available **Boiling point/range** No data available Relative density No data available Vapour pressure No data available Vapour density No data available Partition coefficient: n-octanol/water No data available Viscosity (kinematic) No data available **Evaporation rate** No data available

9.2 Other information No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity Generally non-reactive.

10.2 Chemical stability Stable under normal conditions. 10.3 Possibility of hazardous reactions None if stored and used as directed.

10.4 Conditions to avoid None known.

10.5 Incompatible materials Acids. Strong oxidising agents.

10.6 Hazardous decomposition products Oxides of carbon.

Page 5 of 8 Issued: 13/02/2019; Revision No.1 Regulation (EU) No. 453/2010

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects Acute toxicity

Chemical name	Oral (LD50)	Inhalation (LC50)	Dermal (LD50)
ETHANOL	>10470 mg/Kg (Rat)	>20mg/l (Mouse) 4h	>15800 mg/Kg (Rat)
LIQUEFIED PETROLEUM GAS	Not applicable	>20mg/l (Rat) 4h	Not applicable

Skin corrosion/irritation: Prolonged or repeated contact may cause irritation, skin dryness or cracking.

Serious eye damage/eye irritation: May cause eye irritation.

Respiratory or skin sensitisation: Not expected to be a sensitiser.

Repeated dose toxicity: Not expected to be a hazard.

Carcinogenicity: Not carcinogenic.

Mutagenicity: Not mutagenic.

Toxicity for reproduction: Not expected to be a hazard.

Specific target organ toxicity (STOT): No data available.

Further information The product as a whole may cause irritation of skin, eyes, nose and upper respiratory tract

if exposed to high levels of spray mist.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Chemical name	Species	Test	Value
ETHANOL	Daphnia	EC50 48h	12.34 mg/l
	Golden Orfe	LC50 48h	>100 mg/l
	Algae	EC50 48h	>100 mg/l

Physical properties indicate that petroleum gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice.

12.2 Persistence and degradability Expected to be readily biodegradable.

12.3 Bioaccumulative potentialNo data available

12.4 Mobility in soil Soluble in water.

12.5 Results of PBT and vPvB assessmentContains no PBT or vPvB substances.

12.6 Other adverse effectsMay be harmful to aquatic life if discharged in large quantities into water courses.

Page 6 of 8 Issued: 13/02/2019; Revision No.1 Regulation (EU) No. 453/2010

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal operations: Dispose of in accordance with local and national regulations.

Contact licensed waste disposal company. Most aerosols can be recycled. Do not pierce or burn or use a cutting torch on the empty aerosol container.

14. TRANSPORT INFORMATION

General Information: The UN number for all aerosols is 1950. Aerosols packed in fibreboard cartons up to 30 kg gross weight, or shrink/stretch wrapped onto trays up to 20 kg gross weight may be transported as Limited Quantities, and should display the following symbol on the pack:



The following information relates to all other aerosols not transported as Limited Quantities:

14.1 UN number ADR/RID/ADN; IMDG; ICAO 1950

14.2 UN proper shipping name AEROSOLS

14.3 Transport hazard class(es) ADR/RID/ADN Class 2, 5F

ADR/RID/ADN Class Class 2, Gases

ADR Label No. 2.1

IMDG Class 2

ICAO Class/Division 2

ICAO Subsidiary risk 2.1



Transport labels

14.4 Packing Group ADR/RID/ADN; IMDG; ICAO Not applicable for aerosols

14.5 Environment hazards Marine Pollutant Not applicable for aerosols.

14.6 Special precautions for user EMS F-D, S-U

Tunnel restriction code (D)

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for aerosols.

Page 7 of 8 Issued: 13/02/2019; Revision No.1 Regulation (EU) No. 453/2010

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2001 No.2677) with amendments.

EU Directives

Regulations (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Statutory Instruments

The Chemicals (Hazard information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Guidance Notes

Health and Safety Executive Workplace Exposure Limits EH40.

15.2 Chemical Safety Assessment

Chemical Safety Assessments/Reports (CSA/CSR) are not required for mixtures.

16. OTHER INFORMATION

This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006 (REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals) as amended, and Regulation EU 453/2010.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 (CLP):

Physical hazards: On basis of test data/Expert judgement.

Health hazards: Calculation method Environmental hazards: Calculation method

Full text of H-statements referred to under sections 2 and 3

H220	Extremely	flammable gas.
------	-----------	----------------

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

Page 8 of 8 Issued: 13/02/2019; Revision No.1 Regulation (EU) No. 453/2010

Abbreviations and acronyms

CAS: Chemical Abstract Service (division of the American Chemical Society). {Section 3}.

STOT: Single Target Organ Toxicity (Section 2;11)

SE: Single exposure (Section 2)

DNEL: Derived no effect level – a level above which humans should not be exposed. (Section 8).

PNEC: Predicted No Effect Concentration (Section 8).

TWA: Time-weighted average. (Section 8). STEL: Short-term exposure limit. (Section 8).

PBT: Persistent, Bioaccumulative, Toxic. (Section 12).

vPvB: very Persistent and very Bioaccumulative. (Section 12).

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]