

SAFETY DATA SHEET**PLUS GAS****SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product name PLUS GAS
Product number B1220
Internal identification B1220

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant.

1.3. Details of the supplier of the safety data sheet

Supplier Saint Gobain Abrasives
Doxey Road
Stafford
England
ST16 1EA
www.saint-gobain.co.uk
01785 222000

1.4. Emergency telephone number

Emergency telephone +44 (0) 777 8505 330

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification****Physical hazards**

Not Classified

Health hazards

Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304

Environmental hazards

Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC)

Xn;R65. Xi;R38. N;R51/53. R67.

2.2. Label elements**Pictogram****Signal word**

Danger

Hazard statements

H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H304 May be fatal if swallowed and enters airways.

Precautionary statements

PLUS GAS

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P260 Do not breathe vapour/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.

P501 Dispose of contents/container in accordance with national regulations.

Contains

KEROSINE (PETROLEUM), HYDRODESULFURIZED, WHITE MINERAL OIL (PETROLEUM)

2.3. Other hazards**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

KEROSINE (PETROLEUM), HYDRODESULFURIZED		60-100%
CAS number: 64742-81-0 EC number: 265-184-9 REACH registration number: 01-2119462828-25-xxxx		
Classification	Classification (67/548/EEC or 1999/45/EC)	
Skin Irrit. 2 - H315	Xn;R65. Xi;R38. N;R51/53. R67.	
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
STOT SE 3 - H336		
Aquatic Chronic 2 - H411		
WHITE MINERAL OIL (PETROLEUM)		10-30%
CAS number: 8042-47-5 EC number: 232-455-8 REACH registration number: 01-2119487078-27-XXXX		
Classification	Classification (67/548/EEC or 1999/45/EC)	
Asp. Tox. 1 - H304	Xn;R65.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Ingestion

Rinse mouth thoroughly with water. DO NOT induce vomiting. Get medical attention immediately.

Skin contact

Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

Eye contact

Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed**Inhalation**

Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. Gastrointestinal symptoms, including upset stomach.

Skin contact

Prolonged contact may cause redness, irritation and dry skin.

PLUS GAS

Eye contact

May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with the following media: Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Fire or high temperatures create: Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3. Advice for firefighters

Protective actions during firefighting

No specific firefighting precautions known.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

In case of spills, beware of slippery floors and surfaces. Provide adequate ventilation. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions

Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in closed original container at temperatures between 0°C and 40°C.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PLUS GAS

KEROSINE (PETROLEUM), HYDRODESULFURIZED

Long-term exposure limit (8-hour TWA): OES 300 mg/m³

KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS: 64742-81-0)

DNEL

- Oral; Long term : 19 mg/kg/day

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

No specific ventilation requirements. This product must not be handled in a confined space without adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Rubber (natural, latex). Neoprene. Polyvinyl chloride (PVC).

Hygiene measures

Wash hands after handling.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Clear liquid.

Colour

Colourless.

Odour

Kerosene.

Flash point

> 61°C SCC (Setaflash closed cup).

Relative density

0.815 ± 0.005 @ @ 25°C

9.2. Other information

Other information

Not determined.

SECTION 10: Stability and reactivity

10.1. Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability

Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Not determined.

10.4. Conditions to avoid

PLUS GAS

There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

Harmful: may cause lung damage if swallowed.

Skin contact

Irritating to skin. Repeated exposure may cause skin dryness or cracking.

Eye contact

Irritation of eyes and mucous membranes.

SECTION 12: Ecological Information

Ecotoxicity

The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute toxicity - fish

Not determined.

Ecological information on ingredients.

KEROSINE (PETROLEUM), HYDRODESULFURIZED

Acute toxicity - fish

LC₅₀, 96 hours: 2 - 5 mg/l, Fish

Acute toxicity - aquatic invertebrates

EC₅₀, 48 hours: 1.4 mg/l, Daphnia magna

Acute toxicity - aquatic plants

IC₅₀, 72 hours: 1 - 3 mg/l, Algae

Chronic toxicity - fish early life stage

, 28 days: .098 mg/l, Onchorhynchus mykiss (Rainbow trout)

Chronic toxicity - aquatic invertebrates

, 21 days: 0.89 , Daphnia magna

12.2. Persistence and degradability

Persistence and degradability

The degradability of the product is not known.

12.3. Bioaccumulative potential

The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility

The product has poor water-solubility.

PLUS GAS

12.5. Results of PBT and vPvB assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

Ecological information on ingredients.

KEROSINE (PETROLEUM), HYDRODESULFURIZED

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ENVIRONMENTALLY HAZARDOUS LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS LIQUID, N.O.S. (petroleum distillate)

14.3. Transport hazard class(es)

IMDG class 9

ICAO class/division 9

14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



Yes.

14.6. Special precautions for user

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

PLUS GAS

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance

Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date 30/09/2014

Revision 1.4

Supersedes date 14/05/2014

Risk phrases in full

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.